


ASSEMBLY INSTRUCTIONS

Ortho Comfort Series

Executive High-Back Chair

Model No. 9413AG



PARTS LIST 9413AG


When ordering components, specific color and/or size information may be required.
Contact a Mayline Customer Service Representative. 1-800-822-8037

* Individual Items, Order by part number.

** Denotes Color Code.

| Reference Letter | Quantity | Reference Letter | Quantity |
|---|----------|--|----------|
| A* | 1 | E* | 1 |
| | | | |
| Part Number 102000** Seat Reference Letter | | Part Number 102031 Cylinder Reference Letter | |
| B* | 2 | F* | 1 |
| | | | |
| Part Number 12ADJARM Arms (pair) Reference Letter | | Part Number 102018 Cylinder Cover Reference Letter | |
| C* | 5 | G | 6 |
| | | | |
| Part Number 101400 Castor (5 per pack) Reference Letter | | Screw M6 x 30mm Reference Letter | |
| D* | 1 | H | 1 |
| | | | |
| Part Number 102012 Base Reference Letter | | Part Number 102020* Hardware Bag Reference Letter | |
| | | Quantity | Spare |
| | | 1 | 1 |

1




Tiffany Industries™


A MAYLINE GROUP COMPANY

619 N. Commerce, P.O. Box 728
Sheboygan, WI 53082-0728

Toll Free: 1-800-822-8037
FAX: 920-457-7388
On Line: www.mayline.com




1. Place Base (D) upside down and push Casters (C) firmly into base. 5 places.
2. Turn Base right side up and insert Cylinder (E) into center hole of Base.
3. Place Cylinder Cover (F) over Cylinder.



4. Assemble Arms (B) 2 places onto Seat (A) using Screws (G) 6 places.

2



5. Carefully place chair assembly onto base assembly.

NOTE:

Periodically (Every 90 days) make sure screws are fully tightened.

OPERATING INSTRUCTIONS FOR CENTER PIVOT MECHANISM

1. Seat Height Adjustment.

To raise the seat, rotate lever upward and raise your body up slightly to allow the chair to rise to the desired height.

To lower the seat, rotate lever upward and apply weight downward on the seat.

Seat Upright Lock.


To lock chair in upright position, lean forward and push knob forward chair.

To unlock chair in upright position, lean forward and pull away from chair.

2. Tilt Tension Control Knob.

Turn knob clockwise to increase tilt tension.

Turn knob counter-clockwise to decrease tilt tension.



3